



GARAGE DOOR SYSTEMS.

G·B·D·
CREATIVE AUTOMATIONS

AUTOBOX

230-24V

*PRODUCT ALSO AVAILABLE
AT 115 VAC



©Photographie.eu - stock.adobe.com ▶



AUTOBOX

230-24V *PRODUCT ALSO AVAILABLE AT 115 VAC

Electromechanical operator in 230Vac and 24Vdc for counterweight overhead doors of little and medium dimensions, for residential and condominium use.

EASY TO INSTALL

Thanks to the assembling kit on the door, complete with all the accessories. The motor and limit switches integrated are pre-assembled.

SILENT AND FAST

AUTOBOX is built with gears completely in treated steel and bronze-aluminium, assembled and tested in all its functions. In 24Vdc version, speed is adjustable with soft stop function.

TECHNOLOGICAL AND SAFE

Only high-quality materials, special treatments for the gears and motors tested to last for a long time. Courtesy light and anti-crushing system integrated (24Vdc version). Moreover it is possible to connect the safety devices, as established by EN12453 standards.

A COMPLETE AND RELIABLE RANGE

The different typologies of installation kit allow finding a solution for every kind of door.

COURTESY LIGHT



RELEASE DEVICE

OPEN/CLOSE LIMIT SWITCHES WITH DOUBLE READING



STEEL AND BRONZE GEARS



DOWNLOAD MORE CONTENT




TECHNICAL FEATURES

	AUTOBOX 3000	AUTOBOX 3024
Type of use	RESIDENTIAL	HEAVY DUTY
Frequency of use	30%	40%
Motor power supply	230Vac - 50/60Hz	24 Vdc
Absorbed power	200W	100W
Protection degree	IP40	IP40
Max torque	250 Nm	250 Nm
Shaft rotation speed	7,8°/s	5,6°/s
Adjustable speed	SI	SI
Max door surface	7 sm	7 mq
Operating temperature	-20°C +60°C	-20°C +60°C
On board courtesy light	YES	YES
Encoder/limit switch	LIMIT SWITCHES O/C	LIMIT SWITCHES O/C
Weight of the unit	8,6 Kg	8,6 Kg

APPLICATION DIAGRAM

Single motor application



AUTOBOX 3024 AUTOBOX 3000

DIMENSIONS

