

SWING GATE SYSTEMS.







SWING GATE SYSTEMS.



GROUND

Underground electromechanical operators in 230Vac and 24Vdc, for swinging gates of medium dimensions and weight, for residential and intensive use.

EASY TO INSTALL

Thanks to the special self-supporting foundation box. Ambidextrous motor and pre-assembled accessories.

SILENT AND FAST

Only 12 s to open the gate! Extremely silent, because of the materials chosen and tidy finishing of the gears. In 24Vdc version it is possible to adjust the opening speed.

230-24V *PRODUCT ALSO AVAILABLE AT 115 VAC

TECHNOLOGICAL AND SAFE

GROUND is completely built in steel and bronze-aluminium, is robust and reliable over the time. In 24Vdc version, it is possible to adjust the anti-crushing sensitivity to make the installation safer, as established by EN12453 standards. The unlocking key is with European profile.

A COMPLETE AND RELIABLE RANGE

GROUND satisfies all the esthetical needs of your gate and is reliable over the time, thanks to the reduction gear completely painted, that protects it from the atmospheric and environmental agents.







TECHNICAL FEATURES


Type of useRESIDENTIALHEAVY DUTYFrequency of use30%HEAVY DUTYMotor power supply230 Vac - 50/60 Hz24 VdcAbsorbed power400W150WProtection degreeIP67IP67Shaft rotation speed7°/s7°/sMax torque530 Nm320 NmAdjustable forceELECTRONICELECTRONICAdjustable speedELECTRONIC **ELECTRONIC **Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01		GROUND610	GROUND624
Motor power supply230 Vac - 50/60 Hz24 VdcAbsorbed power400W150WProtection degreeIP67IP67Shaft rotation speed7°/s7°/sMax torque530 Nm320 NmAdjustable forceELECTRONICELECTRONICAdjustable speedELECTRONIC **ELECTRONIC **Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Type of use	RESIDENTIAL	HEAVY DUTY
Absorbed power400W150WProtection degreeIP67IP67Shaft rotation speed7°/s7°/sMax torque530 Nm320 NmAdjustable forceELECTRONICELECTRONICAdjustable speedELECTRONIC **ELECTRONIC **Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Frequency of use	30%	HEAVY DUTY
Protection degreeIP67IP67Shaft rotation speed7°/s7°/sMax torque530 Nm320 NmAdjustable forceELECTRONICELECTRONICAdjustable speedELECTRONIC **ELECTRONIC **Max leaf width3,5 M *3,5 M *Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Motor power supply	230 Vac - 50/60 Hz	24 Vdc
Shaft rotation speed7°/s7°/sMax torque530 Nm320 NmAdjustable forceELECTRONICELECTRONICAdjustable speedELECTRONIC **ELECTRONIC **Max leaf width3,5 M *3,5 M *Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Absorbed power	400W	150W
Max torque530 Nm320 NmAdjustable forceELECTRONICELECTRONICAdjustable speedELECTRONIC **ELECTRONIC **Max leaf width3,5 M *3,5 M *Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Protection degree	IP67	IP67
Adjustable forceELECTRONICELECTRONICAdjustable speedELECTRONIC **ELECTRONIC **Max leaf width3,5 M *3,5 M *Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Shaft rotation speed	7°/s	7°/s
Adjustable speedELECTRONIC **ELECTRONIC **Max leaf width3,5 M *3,5 M *Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Max torque	530 Nm	320 Nm
Max leaf width3,5 M *3,5 M *Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Adjustable force	ELECTRONIC	ELECTRONIC
Max door opening angle110°110°Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Adjustable speed	ELECTRONIC **	ELECTRONIC **
Operating temperature-20°C + 60°C-20°C + 60°CEncoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Max leaf width	3,5 M *	3,5 M *
Encoder/limit switchLS ARE OPTIONALLIMIT SWITCHES O/CType of lubricationGREASE GBD WH-01GREASE GBD WH-01	Max door opening angle	110°	110°
Type of lubrication GREASE GBD WH-01 GREASE GBD WH-01	Operating temperature	-20°C +60°C	-20°C +60°C
	Encoder/limit switch	LS ARE OPTIONAL	LIMIT SWITCHES 0/C
	Type of lubrication	GREASE GBD WH-01	GREASE GBD WH-01
Weight of the unit 11,1 Kg 11,1 Kg	Weight of the unit	11,1 Kg	11,1 Kg

* In case of blind leaf or wind presence or leaf over 2.5 m, the use of the electric lock is necessary

Ø 35

** Control units: BA230 for GROUND610, BA24 for GROUND624


APPLICATION DIAGRAM




INSTALLATION MEASURES

_500

DIMENSIONS







f 💿 오 🕩 ն

GI.BI.DI. S.r.I. Via Abetone Brennero, 177/B 46025 Poggio Rusco (MN) - ITALY Tel. +39.0386.52.20.11 Fax +39.0386.52.20.31 info@gibidi.com

www.gibidi.com